



DATE: December 8, 2025

QUOTE #:361722-01

**CITY OF MESQUITE**  
FRANK RIVERA  
PO BOX 850137  
MESQUITE, TEXAS 75185-0137

**Pemberton, Brent**  
817.219.6187

**One (1) New Caterpillar Inc Model: 140 (Joystick) Motor Grader**

SALE PRICE	\$347,062
EXT WARRANTY	Included
<b>TOTAL PRICE</b>	<b>\$347,062</b>

Quote Through Omnia Contract 212816 - City of Mesquite ID# 4034286

Cat Machine List Price 140 Joystick	\$557,031
OMNIA Discount	-\$167,109
<b>Machine Subtotal</b>	<b>\$389,922</b>
657-8174 CROSS SLOPE ASSIST, TOP ADJUST - OPTION	\$16,500
OMNIA Discount	-\$4,950
<b>Option Subtotal</b>	<b>\$11,550</b>
Machine Prep	\$1,800
Customer Delivery	\$693
Warranty - 84 MO/6000 HR POWERTRAIN + HYDRAULICS	\$9,146
<b>Additional Items/Discount Subtotal</b>	<b>\$11,639</b>
<b>SUBTOTAL</b>	<b>\$413,111</b>
<i>Holt Additional Discount</i>	-\$66,049
<b>GRAND TOTAL</b>	<b>\$347,062</b>
Quote Through Omnia Contract 212816 - City of Mesquite ID# 4034286	

**WARRANTY**

Standard Warranty: 12 Month/Unlimited Hours Total Machine  
Extended Warranty: 84 MO/6000 HR POWERTRAIN + HYDRAULICS

**MACHINE SPECIFICATIONS**

DESCRIPTION	REF.#
140 15A MOTOR GRADER	577-3021
MOLDBOARD, 14' PLUS	349-3048
WEATHER, STANDARD	353-3316
PRECLEANER, NON SY-KLONE	380-6774
ENGINE, TIER IV	567-4685
DRAIN, HIGH SPEED, ENGINE OIL	501-1163
BASE + 1 (RIP)	385-8094
STARTER, ELEC, EXTREME DUTY	395-3547
<b>LIGHTS, ARM, FOLD DOWN</b>	536-9969
<b>LIGHTS, ROADING, LED</b>	550-6608
<b>CAB, PLUS (STANDARD GLASS)</b>	385-9554
<b>CAB, PLUS (INTERIOR)</b>	397-7457
SEAT BELT	394-1492
PRODUCT LINK, CELLULAR PLE742	464-6442
TANK, FUEL, STANDARD	540-2373
FAN, STANDARD, TND	542-4660
TIRES, 17.5R25 BS VKT * D2A MP	252-0775

DESCRIPTION	REF.#
COOLANT, 50/50, -35C (-31F)	469-8157
<b>LIGHTS, WORKING, PLUS, LED</b>	552-7285
LIGHTS, LED STROBE BEACON w/ Mounting Bracket 361-3258	604-3258
LIGHTS, SERVICE, INTERNAL	380-3070
<b>TRANSMISSION, AUTOSHIFT</b>	396-3515
<b>HEADLIGHTS, FRONT, LOW, HALOGEN</b>	308-9370
<b>CAMERA, REAR VISION</b>	396-3921
MIRRORS, OUTSIDE HEATED 24V	344-0984
GUARD, TRANSMISSION	366-2459
CIRCLE SAVER	521-3250
<b>RIPPER ARRANGEMNT</b>	637-6813
<b>SHANKS/TEETH, RIPPER/SCARIFIER</b>	4K-3330
<b>ACCUMULATORS, BLADE LIFT</b>	358-9338
<b>CROSS SLOPE ASSIST, TOP ADJUST</b>	657-8174
<b>CONTROL, AUTO ARTICULATION-FULL</b>	435-2072
<b>JOYSTICK CONTROLS, ADVANCED</b>	458-8701
<b>STABLE BLADE</b>	458-2072

### **637-6813 RIPPER ARRANGEMNT**

Hydraulic, rear mounted ripper with three straight ripper shanks with CapSure CR300 hammerless ripper tips.

Can accommodate two additional ripper shanks and nine scarifier teeth which must be ordered separately.

### **358-9338 ACCUMULATORS, BLADE LIFT**

Provides hydraulic lines for base functions and accumulators for the blade lift. Allows approximately 1-3" of vertical blade travel to reduce impact loads. Nitrogen/oil accumulators activated by electric switch.

### **657-8174 CROSS SLOPE ASSIST, TOP ADJUST ..... 0 \$16,500**

Allows the operator to manually control one end of the moldboard. The system will automatically raise or lower the other end to maintain the desired slope set through the main cab display. Recommended for use in application such as maintaining, crown or shoulder of a road, final grade etc. Provides software, swivel, sensors, harnesses for sensors, mounting for sensors and blade mast brackets.

Also includes industry exclusive E-Fence Blade Avoidance which protects the machine by inhibiting the blade from hitting the tires, ladders, and link bar.

### **435-2072 CONTROL,AUTO ARTICULATION-FULL**

Improves ease of operation, increases maneuverability and maximizes productivity by automatically matching articulation angle to steering angle. Includes 3 position rocker switch enabling 3 modes; off / forward / both forward and reverse.

### **458-8701 JOYSTICK CONTROLS, ADVANCED**

Provides enhanced functionality and additional controls for using Cat Grade ARO, Cross Slope Assist

### **458-2072 STABLE BLADE**

Provides sensor and software to automatically reduce engine speed in various applications to reduce machine bounce and scalloping of surface.

### **396-3515 TRANSMISSION, AUTOSHIFT**

Improves ease of operation and maximizes productivity by automatically shifting the transmission at optimal shift points.

## 521-3250 CIRCLE SAVER

Remote Circle Drive Greasing point (Zerk). Located top of drawbar for easy servicing of circle drive gear. Helps the pinion maintain its lubrication caused by lack of grease in this component.

## STANDARD EQUIPMENT

---

### POWERTRAIN

Air cleaner, dual stage dry type radial seal with service indicator and automatic dust ejector  
Air-to-air after cooler (ATAAC)  
Belt, serpentine, automatic tensioner  
Brakes, oil disc, four-wheel, hydraulic  
Demand fan, hydraulic  
Differential, lock/unlock, Automatic  
Drain, engine oil, ecology

Electronic over-speed protection  
Parking brake, multi-disc, sealed and oil cooled.  
Sediment drain, fuel tank.  
Transmission, 8 speed forward and 6 speed reverse, power shift, direct drive  
VHP Plus (Variable Horse Power Plus)

### ELECTRICAL

Alarm, back-up  
Alternator, 150 ampere, sealed  
Batteries, maintenance free, heavy duty, 1125 CCA  
Breaker panel, ground accessible  
Electrical hydraulic valves  
Electrical system, 24V

Grade Control Ready (Cab harness, software, electrical hydraulic valves, bosses and brackets)  
Lights, reversing  
Lights, roading, roof-mounted, stop and tail, LED  
Starter, electric

### OPERATOR ENVIRONMENT

Air Conditioning with heater  
Articulation, automatic return to center  
Centershift pin indicator  
Display, digital speed and gear  
Doors, left and right side with wiper  
Gauge, machine level  
Gauges (analog) inside the cab (includes fuel, articulation, engine coolant temp, engine RPM, and hydraulic oil temp, DEF/AdBlue)  
Joystick, adjustable armrests  
Joystick gear selection, hydraulic power steering hydraulic controls (right/left, blade lift w/ float position, blade sideshift and tip, circle drive, centershift, front wheel lean and articulation and steering)  
Lights, night time cab

Messenger operator information system  
Meter, hour, digital  
Mirror, inside rearview, wide angle  
Power port, 12V  
Radio ready, entertainment  
ROPS cab, sound suppressed - 69dB(A) - ISO 6394  
Seat, cloth-covered, comfort suspension  
Storage area for cooler/lunchbox  
Throttle control, electronic  
Windows laminated glass:  
-Fixed front with intermittent wiper  
-Door with intermittent wipers (3)  
Windows tempered:  
-Left and right side wipers  
-Rear with intermittent wiper  
Cab storage

### SAFETY AND SECURITY

Clutch, circle drive slip  
Doors, 2 engine compartment, (two left hand, two right hand) locking  
Doors, 2 service, left and right locking  
Ground level engine shutdown  
Hammer (emergency exit)

Horn, electric  
Lockout, hydraulic implement (for roading and servicing)  
Seat belt, retractable 76.2 (3")  
Secondary steering  
Tandem walkway/guards

### TIRES, RIMS, AND WHEELS

A partial allowance for tires on 254mm x 609.6mm (10" x 24") multi-piece

### FLUIDS

Antifreeze

### OTHER STANDARD EQUIPMENT

Accumulators -brake -dual certified  
Drawbar, 6 shoe w/replaceable wear strips  
Fluid check, ground level  
Fuel tank, 398 liters (105 gallon)  
Ground level fueling  
DEF/AdBlue Tank, 21 liters (5.5 gallon)

Extended life coolant -35C/-30F  
(98cc / 15 cu in)  
Radiator, cleanout access (both sides with swing doors)  
SOS ports - engine -hydraulic transmission -coolant -fuel  
Tool box

Hydraulic lines for base functions  
Pump, hydraulics, high capacity

Debris guard